


FLOOR SAW FSD1061 ★★

CUTTING DEPTHS UP TO 410 MM



Two precisely coordinated drive shafts make it possible to work with different saw blade diameters in the optimum speed range



Ergonomic working position



Practical universal blade guard makes left and right cutting possible, and also flush cutting for corners

- High productivity and service life due to well-ried and extremely robust design
- Excellent cutting performance due to intelligent weight distribution
- Coordinated working with different saw blade diameters thanks to two drive shafts
- Convenient, ergonomic operation using hydraulic feed drive and electro-hydraulic cutting depth adjustment
- Additional flexibility due to left and right cutting function and flush cutting function for corners
- Problem-free, safe transport using sturdy transport hooks
- Service-friendly machine design
- Maximum safety due to centrally located emergency stop switch and integrated brake
- Precise cut guidance from standard cut indicator at front and rear
- Optionally with diesel particle filter and fresh concrete set

Technical data

SAW BLADE	
Max. cutting depth	410 mm
Max. saw blade Ø	1,000 mm
Saw blade speed	1,005/1,460 rpm
Saw blade holder Ø	25.4 mm
Carrier Ø	11.5 mm
Reference circle Ø	57.4 mm

DRIVE	
Drive/motor	Diesel
Type	Deutz
Output	45 kW / 61 HP
Fuel	Diesel
Fuel tank	34.2 l
Engine cooling	Air cooling
Feed	Hydraulic
Blade drive	Via V-belt
Feed speed	0-61 m/min.

DESIGN	
Electro-hydraulic cutting depth adjustment	
Cutting depth indicator	
Tool cooling using water fork	
Left/right cutting function	
Corner flush cutting function	

DIMENSIONS & WEIGHT	
Length	1,390 mm
Width	970 mm
Height	1,290 mm
Weight	890 kg

System & accessories

FLOOR SAW FSD1061**		
10984044	Floor saw FSD1061S	

ACCESSORIES		
10984392	Green concrete kit with 500 mm blade guard and transformation set (2100 rpm)	

Diesel particle filter and transformation set on request