

FLOOR SAW FSD930★★

CUTTING DEPTHS UP TO 350 MM



Easy, controlled working thanks to clearly arranged controls



Water regulation for optimum tool cooling, and useful lighting always close by



Machine is exactly aligned using cut indicator

- High productivity and service life due to well-ried and extremely robust design
- Excellent cutting performance due to intelligent weight distribution
- Convenient, ergonomic operation using hydraulic feed drive and electro-hydraulic cutting depth adjustment
- Additional flexibility due to left and right cutting function and corner flush cutting function
- Problem-free, safe transport using sturdy transport hooks
- Service-friendly machine design
- Maximum safety due to centrally located emergency stop switch and integrated brake
- Precise cut guidance from standard cut indicator at front and rear
- Optionally with diesel particle filter, fresh concrete set and transformation set

Technical data

SAW BLADE	
Max. cutting depth	350 mm
Max. saw blade Ø	900 mm
Saw blade speed	1,165 rpm
Saw blade holder Ø	25.4 mm
Carrier Ø	11.5 mm
Reference circle Ø	57.4 mm

DRIVE	
Drive/motor	Diesel
Type	Deutz
Output	22 kW / 30 HP
Fuel	Diesel
Fuel tank	22.8 l
Engine cooling	Air cooling
Feed	Hydraulic
Blade drive	Via V-belt
Feed speed	0-61 m/min.

DESIGN	
Electro-hydraulic cutting depth adjustment	
Cutting depth indicator	
Tool cooling using water fork	
Left/right cutting function	
Corner flush cutting function	

DIMENSIONS & WEIGHT	
Length	1,280 mm
Width	810 mm
Height	1,180 mm
Weight	612 kg

System & accessories

FLOOR SAW FSD930**		
10984042	Floor saw FSD930S	

ACCESSORIES		
10984390	Green concrete kit with 450 mm blade guard and transformation set (2300 rpm)	

Diesel particle filter and transformation set on request