


FLOOR SAW FSD961 ★★

CUTTING DEPTHS UP TO 350 MM



Left and right saw blade attachment function provides additional flexibility



Practical universal blade guard provides left and right cutting function and also flush cutting for corners



User-friendly controls make handling easier work monitoring easier

- High productivity and service life due to well-ried and extremely robust design
- Excellent cutting behaviour thanks to high-torque motor
- Convenient, ergonomic operation using hydraulic feed drive and electro-hydraulic cutting depth adjustment
- Additional flexibility due to left and right cutting function and flush cutting function for corners
- Problem-free, safe transport using sturdy transport hooks
- Service-friendly machine design
- Maximum safety due to centrally located emergency stop switch and integrated brake
- Precise cut guidance from standard cut indicator at front and rear
- Optionally with diesel particle filter, fresh concrete set and transformation set

The Tyrolit logo, consisting of the word "TYROLIT" in a bold, blue, sans-serif font with a blue underline.

Technical data

SAW BLADE	
Max. cutting depth	350 mm
Max. saw blade Ø	900 mm
Saw blade speed	1,161 rpm
Saw blade holder Ø	25.4 mm
Carrier Ø	11.5 mm
Reference circle Ø	57.4 mm

DRIVE	
Drive/motor	Diesel
Type	Deutz
Output	45 kW / 61 HP
Fuel	Diesel
Fuel tank	34.2 l
Engine cooling	Air cooling
Feed	Hydraulic
Blade drive	Via V-belt
Feed speed	0-61 m/min.

DESIGN	
Electro-hydraulic cutting depth adjustment	
Cutting depth indicator	
Tool cooling using water fork	
Left/right cutting function	
Corner flush cutting function	

DIMENSIONS & WEIGHT	
Length	1,390 mm
Width	970 mm
Height	1,290 mm
Weight	727 kg

System & accessories

FLOOR SAW FSD961**		
10984043	Floor saw FSD961S	

ACCESSORIES		
10984391	Green concrete kit with 500 mm blade guard and transformation set (2100 rpm)	

Diesel particle filter and transformation set on request