

FLOOR SAW FSG513 ★★★

CUTTING DEPTHS UP TO 170 MM



User friendly depth of cut setting and simple speed control



Optimised centre of gravity over the cutting shaft



Universal operation with left and right cutting function

- Excellent cutting performance due to intelligent weight distribution
- Easy handling due to ergonomically arranged operating elements
- High load resistance and vibration reduction thanks to robust, high quality chassis
- Increased flexibility due to left and right hand cutting functions as well as corner flush cutting function
- Problem free and safe transport by means of a balanced transport hook
- Optimum tool cooling using reliable water supply
- Service friendly machine construction
- Reliable Honda petrol engine with cyclone filter
- Precise cutting guide using a standard cut indicator
- Maximum safety by using a centrally positioned emergency stop switch and integrated brake

Technical data

SAW BLADE	
Max. cutting depth	170 mm
Max. saw blade Ø	450 mm
Saw blade speed	2600 1/min
Saw blade uptake Ø	25.4 mm
Carrier Ø	11.5 mm
Reference circle Ø	57.4 mm

DRIVE	
Drive/motor	Petrol
Type	Honda
Power	8.2 kW / 11 PS
Fuel	Lead free
Fuel tank	6.1 l
Engine cooling	Air cooling
Feed	Manual
Blade drive	Via V-belt

DESIGN	
Manual, cutting depth adjustment via spindle	
Cutting depth indicator	
Tool cooling using water fork	
Left and right hand cutting function	
Flush corner cut function	
25 l water tank	

DIMENSIONS & WEIGHT	
Length	1136 mm
Width	578 mm
Height	1016 mm
Weight	113 kg

System & Accessories

FLOOR SAW FSG513***		
10988500	Floor saw FSG513P	
10988800	Floor saw FSG513P incl. water tank kit	

ACCESSORIES		
10988783	Water tank kit (water tank holder, water tank, hook for transport)	