

FLOOR SAW FSG620★★

CUTTING DEPTHS UP TO 230 MM



Easy handling due to clearly arranged operating elements



Controlled working thanks to digital operating hours counter and reliable petrol gauge



Blade guard side change possible with a few manual operations

- Convenient operation using hydraulic feed drive
- Excellent cutting performance due to intelligent weight distribution
- Additional flexibility due to left and right cutting function
- Problem-free, safe transport using sturdy transport hooks
- Easy, smooth cutting depth adjustment using precise and protected spindle
- Maximum safety due to centrally located emergency stop switch and integrated brake
- Reliable, easy to maintain Honda petrol motor
- Precise cut guidance by standard cut indicator
- Optional fresh concrete set

TYROLIT

Technical data

SAW BLADE	
Max. cutting depth	230 mm
Max. saw blade Ø	600 mm
Saw blade speed	1,590 rpm
Saw blade holder Ø	25.4 mm
Carrier Ø	11.5 mm
Reference circle Ø	57.4 mm

DRIVE	
Drive/motor	Petrol
Type	Honda
Output	15 kW / 20 HP
Fuel	Lead free
Fuel tank	7.6 l
Engine cooling	Air cooling
Feed	Hydraulic
Blade drive	Via V-belt
Feed speed	0-24 m/min.

DESIGN	
Manual, stepless cut depth setting via a spindle	
Tool cooling using water fork	
Left/right cutting function	
19 l water tank	

DIMENSIONS & WEIGHT	
Length	990 mm
Width	570 mm
Height	1,070 mm
Weight	200 kg

System & accessories

FLOOR SAW FSG620**		
10984041	Floor saw FSG620S	

ACCESSORIES		
10984389	Green concrete kit with 350 mm blade guard and transformation set (3000 rpm)	