

FLOOR SAW HFS1030RC

CUTTING DEPTHS UP TO 420 MM



Simple to control using remote control



Increased safety aspect due to power connection with water spray protection



Universal blade guard provides completely clean cutting right into corners

- Wide range of uses and problem-free transport due to intelligent compact design
- Convenient operation thanks to electric feed and electric cutting depth adjustment (using remote control)
- Quick and easy change from left to right cutting
- Service-friendly machine design
- Maximum safety due to centrally located emergency stop switch and integrated brake
- Precise cut guidance by standard cut indicator
- Optional flush wall cutting kit

Technical data

SAW BLADE	
Max. cutting depth	420 mm (520 mm)
Max. saw blade Ø	1,000 mm (1,200 mm)
Saw blade speed	700-2,700 rpm
Saw blade holder Ø	25.4 mm
Carrier Ø	11.5 mm
Reference circle Ø	57.4 mm

DRIVE	
Drive/motor	Electrical (frequency converter)
Output	22 kW
Voltage	400 V
Cooling	Air cooling
Feed	Electric
Blade drive	Via V-belt
Feed speed	0-33 m/min.

DESIGN	
Electric cutting depth adjustment	
Cutting depth indicator	
Tool cooling using flange	
Left/right cutting function	
Corner flush cutting function	
Remote control	

DIMENSIONS & WEIGHT	
Length	1,180 mm
Width	720 mm
Height	960 mm
Weight	459 kg

System & accessories

FLOOR SAW HFS1030RC		
10981256	Floor saw HFS1030RC	

ACCESSORIES		
10978774	Flush cutting flange	
10978988	Protection cover for blade Ø 1200 mm	