

FLOOR SAW HFS811

CUTTING DEPTHS UP TO 320 MM



Transmission gearing guarantees optimum cutting speeds



Easy loading and transportation of the machine by dismantling into individual parts



Cleverly devised transport system makes the equipment easier to use, particularly indoors

- Maximum mobility due to cleverly devised modular design
- Optimum suitability for deployment locations that are difficult to access
- Quick and easy change from left to right cutting
- Smooth cutting depth adjustment using precise and protected spindle
- Maximum safety due to centrally located emergency stop switch and integrated brake
- Precise cut guidance by standard cut indicator
- Optional flush wall cutting kit

Technical data

SAW BLADE	
Max. cutting depth	320 mm
Max. saw blade Ø	800 mm
Saw blade speed	1,250 rpm
Saw blade holder Ø	25.4 mm
Carrier Ø	11.5 mm
Reference circle Ø	57.4 mm

DRIVE	
Drive/motor	Electric
Output	7.5 kW
Voltage/frequency	400 V / 50 Hz
Engine cooling	Air cooling
Feed	Manual
Blade drive	Via V-belt

DESIGN	
Manual, stepless cut depth setting via a spindle	
Cutting depth indicator	
Tool cooling using flange	
Left/right cutting function	
Corner flush cutting function	

DIMENSIONS & WEIGHT	
Length	1,100 mm
Width	600 mm
Height	980 mm
Weight	158 kg

System & accessories

FLOOR SAW HFS811		
10981255	Floor saw HFS811	

ACCESSORIES		
10978775	Flush cutting flange	
10978776	Protection cover flush cutting flange	