

# DRIVE UNIT DK-S

OUTPUT 48 HP



Detachable hydraulic control unit



4 settings for ideal cutting speed



Robust control and operating elements

- Suitable for wall saws, wire saws and drilling
- Ideal cutting speed due to having 4 settings
- Extremely suitable for construction sites without a power connection thanks to the turbo diesel motor

The logo for Tyrolit, featuring the word "TYROLIT" in a bold, blue, sans-serif font with a slight upward curve at the bottom.

## Technical data

DIESEL MOTOR	
Output	48 HP

  

HYDRAULICS	
Pressure stages	4
2 feed circuits	Radial piston pump
Main circuit	Quadruple gear pump

  

OUTPUT	
Stage 1	60 l/min at 240 bar
Stage 2	70 l/min at 200 bar
Stage 3	80 l/min at 160 bar
Stage 4	90 l/min at 130 bar

  

DIMENSIONS	
Length	1,400 mm
Width	790 mm
Height	1,320 mm
Weight	440 kg

## System & accessories

DRIVE UNIT DK-S		
977252	Drive unit DK-S (Kubota Diesel)	
975729	Remote control BS	
976207	Hose package 3pieces 8 m FD	
974066	Leakage oil hose 8 m FIRG	
975672	Hose package 2pieces 8 m FF (feed)	
975672	Hose package 2pieces 8 m FF (feed)	

  

ACCESSORIES		
976205	Hose package 4pieces 16 m FD	
977227	Leakage oil hose 16 m (DK-S, RD-S)	