

# DRIVE UNIT PPH20 ★★★

OUTPUT 20 KW



Ergonomically arranged control elements



Safe because of top quality electrical components



The plastic cover can be removed without tools

- Suitable for wall saws, wire saws and drilling
- Ideal cutting speed due to having 4 settings
- Robust, reliable structure
- Current rotating direction easy to reverse using rotating direction switch
- Service-friendly thanks to quick-release plastic cover



## Technical data

ELECTRIC MOTOR	
Output	20 kW

  

HYDRAULICS	
Pressure stages	4
2 feed circuits	Radial piston pump
Main circuit	Triple gear pump

  

OUTPUT	
Stage 1	33 l/min at 260 bar
Stage 2	40 l/min at 215 bar
Stage 3	50 l/min at 180 bar
Stage 4	60 l/min at 150 bar

  

ELECTRICAL EQUIPMENT	
Voltage	200 V / 230 V / 380 V / 400 V / 460 V
Frequency	50 Hz / 60 Hz
Current consumption (400 V)	32 A
2 secondary connections, rotating direction switch	

  

DIMENSIONS	
Length	760 mm
Width	550 mm
Height	1,140 mm
Weight	135 kg

## System & accessories

DRIVE UNIT PPH20***		
10983200	Drive unit PPH20P / 380-420V / 50Hz	
976206	Hose package 5pieces 8 m FD	
975672	Hose package 2pieces 8 m FF (feed)	

  

VOLTAGE VARIATIONS		
10983200	Drive unit PPH20P / 380-420V / 50Hz	
10984005	Drive unit PPH20P / 200-220V / 50Hz	
10984003	Drive unit PPH20P / 200-240V / 60Hz	
10984668	Drive unit PPH20P / 420-480V / 60Hz	
10984004	Drive unit PPH20P / 380V / 60Hz	
10984669	Drive unit PPH20P / 230V / 50Hz	

  

ACCESSORIES		
973072	El.-plug CEE 32/5pol.	