

DRIVE UNIT PPH20RR ★★★

OUTPUT 20 KW



Freedom of movement thanks to radio remote control. All functions selectable via radio remote control



Direction of rotation switch, secondary connections, hour counter



The plastic cover can be removed without tools

- Suitable for wall saws, wire saws and drilling
- Ideal cutting speed due to having 4 settings
- Soft start of wire using potentiometer
- Service-friendly thanks to quick-release plastic cover



Technical data

ELECTRIC MOTOR	
Output	20 kW
HYDRAULICS	
Pressure stages	4
2 feed circuits	Radial piston pump
Main circuit	Triple gear pump
OUTPUT	
Stage 1	33 l/min at 260 bar
Stage 2	40 l/min at 215 bar
Stage 3	50 l/min at 180 bar
Stage 4	60 l/min at 150 bar
ELECTRICAL EQUIPMENT	
Voltage	200 V / 230 V / 320 V / 400 V / 460 V
Frequency	50 Hz / 60 Hz
Current consumption (400 V)	32 A
2 secondary connections, rotating direction switch	
DIMENSIONS	
Length	760 mm
Width	550 mm
Height	1,140 mm
Weight	160 kg

System & accessories

DRIVE UNIT PPH20RR***		
10983500	Drive unit PPH20RRP / 380-420V / 50Hz / Freq. 434MHz	
976206	Hose package 5pieces 8 m FD	
975672	Hose package 2pieces 8 m FF (feed)	
VOLTAGE VARIATIONS		
10983500	Drive unit PPH20RRP / 380-420V / 50Hz / Freq. 434MHz	
10984546	Drive unit PPH20RRP / 380-420V / 50Hz / Freq. 458MHz	
10984547	Drive unit PPH20RRP / 380-420V / 50Hz / Freq. 419MHz	
10984654	Drive unit PPH20RRP / 200-220V / 50Hz / Freq. 429MHz	
10984655	Drive unit PPH20RRP / 420-480V / 60Hz / Freq. 458MHz	
10984656	Drive unit PPH20RRP / 200-240V / 60Hz / Freq. 434MHz	
10984657	Drive unit PPH20RRP / 200-240V / 60Hz / Freq. 458MHz	
10984658	Drive unit PPH20RRP / 200-240V / 60Hz / Freq. 429MHz	
10984659	Drive unit PPH20RRP / 380V / 60Hz / Freq. 434MHz	
10984660	Drive unit PPH20RRP / 380V / 60Hz / Freq. 447MHz	
10984661	Drive unit PPH20RRP / 230V / 50Hz / Freq. 434MHz	
ACCESSORIES		
973072	El.-plug CEE 32/5pol.	