

DRIVE UNIT PPH25RR ★★★

OUTPUT 25 KW



Freedom of movement thanks to radio remote control. All functions selectable via radio remote control



Pressure stages selectable using rotary switch



The plastic cover can be removed without tools

- Suitable for wall saws, wire saws and drilling
- Ideal cutting speed due to having 4 settings
- Soft start of wire using potentiometer
- Service-friendly thanks to quick-release plastic cover

The Tyrolit logo is displayed in a bold, blue, stylized font with a white outline.

Technical data

ELECTRIC MOTOR	
Output	25 kW

HYDRAULICS	
Pressure stages	4
2 feed circuits	Radial piston pump
Main circuit	Triple gear pump

OUTPUT	
Stage 1	45 l/min at 230 bar
Stage 2	50 l/min at 200 bar
Stage 3	60 l/min at 170 bar
Stage 4	70 l/min at 140 bar

ELECTRICAL EQUIPMENT	
Voltage	380 V / 400 V
Frequency	50 Hz
Current consumption (400 V)	42 A
2 secondary connections, rotating direction switch	

DIMENSIONS	
Length	760 mm
Width	550 mm
Height	1,140 mm
Weight	170 kg

System & accessories

DRIVE UNIT PPH25RR***		
10983900	Drive unit PPH25RRP / 380-420V / 50Hz / Freq. 434MHz	
976206	Hose package 5pieces 8 m FD	
975672	Hose package 2pieces 8 m FF (feed)	

VOLTAGE VARIATIONS		
10983900	Drive unit PPH25RRP / 380-420V / 50Hz / Freq. 434MHz	
10984544	Drive unit PPH25RRP / 380-420V / 50Hz / Freq. 458MHz	
10984545	Drive unit PPH25RRP / 380-420V / 50Hz / Freq. 419MHz	

ACCESSORIES		
973074	El.-plug CEE 63/5pol.	