

DRIVE UNIT PPH25 ★★

POWER 25 KW



Ergonomically arranged control elements



Safer due to use of high quality electric components



Pressure gauges for main and feed circuits

- Suitable for wall sawing, wire sawing and drilling
- Ideal cutting speed using 2 stage adjustment
- Simple operation directly at the equipment with few hand movements
- Service-friendly thanks to plastic cover

The Tyrolit logo, consisting of the word 'TYROLIT' in a bold, blue, sans-serif font with a slight upward curve at the bottom.

Technical data

ELECTRIC MOTOR	
Power	25 kW

HYDRAULIC	
Pressure stages	2
2 feed circuits	Gear wheel
Main circuit	Simple gear pump

POWER	
Stage 1	45 l/min at 230 bar
Stage 2	50 l/min at 200 bar

ELECTRIC	
Voltage	400 V / 460 V
Frequency	50 Hz / 60 Hz
Current consumption (400 V)	42 A
Forward/reverse switch	

DIMENSIONS	
Length	720 mm
Width	475 mm
Height	988 mm
Weight	145 kg

System & Accessories

DRIVE UNIT PPH25**		
10984200	Drive unit PPH25S / 380-420 V / 50 Hz	
976206	Hose package 5pieces 8 m FD	
975672	Hose package 2pieces 8 m FF (feed)	

DIFFERENT VOLTAGE VERSIONS		
10984200	Drive unit PPH25S / 380-420 V / 50 Hz	
10984800	Drive unit PPH25S / 440-480 V / 60 Hz	

ACCESSORIES		
973074	El.-plug CEE 63/5pol.	
999578	On/Off valve for wire sawing	