

DRIVE UNIT PPH40RR ★★★

OUTPUT 40 KW



Freedom of movement thanks to radio remote control. All functions selectable via radio remote control



Direction of rotation switch, secondary connections, hour counter



The plastic cover can be removed without tools

- Suitable for wall saws, wire saws and drilling
- Ideal cutting speed due to having 4 settings
- Soft start of wire using potentiometer
- Service-friendly thanks to quick-release plastic cover

The Tyrolit logo, consisting of the word 'TYROLIT' in a bold, blue, sans-serif font with a slight upward curve at the bottom.

Technical data

ELECTRIC MOTOR	
Output	40 kW
HYDRAULICS	
Pressure stages	4
2 feed circuits	Radial piston pump
Main circuit	Triple gear pump
OUTPUT	
Stage 1	65 l/min at 250 bar
Stage 2	75 l/min at 220 bar
Stage 3	80 l/min at 200 bar
Stage 4	90 l/min at 180 bar
ELECTRICAL EQUIPMENT	
Voltage	380 V / 400 V / 460 V / 575 V
Frequency	50 Hz / 60 Hz
Current consumption (400 V)	60 A
2 secondary connections, rotating direction switch	
DIMENSIONS	
Length	820 mm
Width	560 mm
Height	1,260 mm
Weight	238 kg

System & accessories

DRIVE UNIT PPH40RR***		
10983400	Drive unit PPH40RRP / 380-420V / 50Hz / Freq. 434MHz	
975672	Hose package 2pieces 8 m FF (feed)	
975672	Hose package 2pieces 8 m FF (feed)	
976207	Hose package 3pieces 8 m FD	
VOLTAGE VARIATIONS		
10983400	Drive unit PPH40RRP / 380-420V / 50Hz / Freq. 434MHz	
10984548	Drive unit PPH40RRP / 380-420V / 50Hz / Freq. 458MHz	
10984549	Drive unit PPH40RRP / 380-420V / 50Hz / Freq. 419MHz	
10984651	Drive unit PPH40RRP / 380V / 60Hz / Freq. 434MHz	
10984652	Drive unit PPH40RRP / 380V / 60Hz / Freq. 447MHz	
10984001	Drive unit PPH40RRP / 460V / 60Hz / Freq. 458MHz	
10984002	Drive unit PPH40RRP / 575V / 60Hz / Freq. 458MHz	
ACCESSORIES		
973074	El.-plug CEE 63/5pol.	